



T = Terminal Splice Point provides Splice point for customer hook up
 V = Vault for protecting Conduit under road
 S= Slack Vault for extra Fiber
 All Vaults 24" x 36" x 24" or 17" x 33" x 24"
 Vault flush with ground level. These notes apply to all sheets

All road crossings 48" depth
 All road laterals 36" depth
 It is anticipated that most laterals will be knifing. Vaults will be placed in line with driveways. Driveways will be utilized to assist boring across the road. This technique will significantly reduce the impact on vegetation.

Vaults are placed to minimize road way disturbance both for setting boring machine and delivering drop cable between household and Vault. Vaults at end of common drives.

Conduit at roadway edge as close to tree line as physically possible. feet from road center line based on existing utilities

Where practical drops may be bored to the home or may be placed at 18" using a small plow following the driveway. Placement and path of drop to home is discussed with household. Vaults at drive for drops may be at edge of road right of way.

| | | | |
|-------------------------------------|--------|---------------------|-----------------|
| Cherry Capital Connection | | | |
| Natural Beauty Road Overview | | | |
| Project: LLC - GP-Natural-Beauty | | | |
| Location: Gills Pier road | | | |
| Twn: 1 | Rng: 2 | Section: 3 | Sheet: 01 of 09 |
| Tax District: Leelanau | | County: Leelanau | |
| Eng By: Tim M | | Printed: 2020-10-07 | |