



T = Terminal Splice Point provides Splice point for customer hook up  
 V = Vault for protecting Conduit under road  
 S = Slack Vault for extra Fiber  
 All Vaults 24" x 36" x 24" or 17" x 33" x 24"  
 Vault flush with ground level

All road crossings 48" depth  
 All road laterals 36" depth  
 IT is anticipated that most lateral will require boring. Small brush will need to be removed for placement of the boring machine. Care will be taken to minimize the placement to reduce vegetation removal. Vault is flush allowing vegetation to grow over the vault.

Vaults are placed to minimize road way disturbance both for setting boring machine and delivering drop cable between household and Vault. Vault may be added if it will reduce impact on environment from drop cable placement

Boring machine can bore 400 feet. If there are multiple vaults within the reach of 400 feet CCC will hand dig the placement of the vault. Conduit 25-33 feet from road center line based on existing utilities

Where practical drops may be bored to the home or may be placed at 18" using a small plow following the driveway. Placement and path of drop to home is discussed with household

<b>Cherry Capital Connection</b>			
<b>Natural Beauty Road Overview</b>			
Project: LLC - GP-Natural-Beauty			
Location: Gills Pier road			
Twn: 1	Rng: 2	Section: 3	Sheet: 01 of 09
Tax District: Leelanau		County: Leelanau	
Eng By: Tim M			Printed: 2020-08-24